

nora® INDUSTRY/LIFE SCIENCES APPLICATIONS

The Recommended Application Chart* is based on industry best-practices and intended to be used in conjunction with local building codes/requirements and FGI guidelines. This chart is a working document and will be updated periodically. Specialized site conditions or goals can affect recommendations. Please contact your Industry Key Account Director with questions or additional information.

	norament® tile								noraplan® tile/sheet				
	825 round, hammered	arago™, castello™, kivo™, pado™	grano™, satura™	grano™ ed	xp™	xp trac™	920	992, 992 grano™	convia™, dariva™, environcare™, sentica™ (2 mm)	dariva, environcare, sentica (3 mm)	environcare™ acoustic, sentica™ acoustic	environcare™ ed, sentica™ ed	unita™, valua™ (2 mm & 3 mm)
Assembly	—	—	✓	✓ ■	✓	✓	—	—	—	✓	—	✓ ■ Δ	—
Atrium	—	✓	✓	—	✓	—	—	—	✓	✓	—	—	✓
Cafeteria	✓	✓	✓	—	✓	—	—	—	✓	✓	—	—	✓
cGMP Production Areas (including production stairwells)	—	—	—	✓ ■	✓	✓	—	—	—	—	—	—	—
Cleanroom	—	—	✓	✓ ■	✓	✓	—	—	✓	✓	—	✓ ■	—
Corridors	✓	✓	✓	✓ ■	✓	—	—	—	✓	✓	—	✓ ■	✓
Dressing/Locker Rooms	✓	✓	✓	—	✓	✓	—	—	✓	✓	—	—	✓
Entrance Areas	—	✓	✓	—	✓	—	—	—	✓	✓	—	—	✓
ESD Areas	—	—	—	✓ ■	—	—	—	—	—	—	—	✓ ■	—
Laboratories/Research	—	✓	✓	✓ ■	✓	—	—	✓ ◇	✓	✓	—	✓ ■	—
Machine Shop (oil)	—	—	✓	✓ ■	—	—	✓	—	—	—	—	—	—
Manufacturing	✓	—	✓	✓ ■	✓	✓	✓	—	—	—	—	✓ ■ Δ	—
Office Areas/Conference Rooms	—	✓	✓	—	—	—	—	—	✓	✓	—	—	✓
Processing Areas	—	—	✓	✓ ■	✓	✓	—	—	—	—	—	✓ ■	—
Stairwells (excluding production stairwells)	✓ 1	✓	✓	—	—	—	✓	—	✓	✓	—	—	✓
Warehouse (forklift)	—	—	✓ †	✓	✓ †	—	✓	✓	—	—	—	—	—

Updated: November 2023

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

KEY:

✓ = Yes (recommended)

— = No (not recommended)

Δ = Not suitable for forklift traffic

◇ = Large animal spaces and LN2 resistance

■ = Use conductive adhesive and copper tape with ed products

† = Must use nora® 2-part adhesive

1 = Expect a color variation when pairing norament 825 round/hammered tiles with norament round/hammered stairtreads

2 = Striated profile surface is recommended

*Not inclusive of all potential space applications