

nora heat weld

Developed for use with noraplan® floor coverings. As nora® floor coverings do not contain volatile phthalate plasticizers and do not shrink after installation, welding is not required. One exception is noraplan acoustic, which is required due to its resilient structure. Welding is recommended for special applications such as: rooms with continual and intensive wet cleaning, areas with stringent requirements for hygiene, and areas with special requirements like operating rooms and laboratories.



Product Data

Product: nora® heat weld, Article 946

Description: An EVA-copolymer with pigments for sealing nora rubber floor coverings.

Characteristics:

- Size/description: Round .16" (4.0 mm) welding rod on a cardboard reel.
- Colors: Can be delivered for all noraplan colors. Contact your nora Sales Representative for availability.

Technical Data

Shelf Life:	Minimum 5-years
Application:	Hot air welding gun with 4.0 mm speed tip
Coverage:	~ 328 linear feet (100 linear meters)
Storage:	Room temperature and away from direct sunlight

Environmental Attributes

Carbon: All flooring products 3rd party verified carbon neutral throughout their entire life cycle through the Interface Carbon Neutral Floors™ program. Learn more at www.interface.com/carbonneutral.

Material Composition: Free of organic solvents, formaldehyde, asbestos, lindane, rosins, phthalates, or any other volatile components.

VOC Content: <12 grams/liter. In compliance with the SCAQMD Rule 1168 Standard for Architectural Sealants, which has a VOC limit of 250 grams/liter.

LEED: Meets VOC emissions and content requirements of LEED.

Installation

Site Conditions: The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.

Substrate Requirements: Concrete, wood, metal, and existing floors (existing floors must be only one layer and non-cushioned back); refer to the nora Installation Instructions for details.

Unique Characteristics:

- Excellent for heavy traffic
- Non-flammable
- Designed for use with noraplan flooring; contact a nora Technical Specialist for use with norament® flooring
- Review adhesive instructions to determine when heat welding of flooring can commence

For complete installation instructions refer to the nora Installation Instructions.

Disclaimer

It is the user's responsibility to read, understand and follow the nora Installation Instructions, Product Data Sheet, and Safety Data Sheet available on www.nora.com. You should comply with all applicable OSHA, local, state, and federal regulations.

Clean-up

Do not allow heat weld to cool on the flooring surface. It may be possible to remove heat weld by reheating, but some surface damage may occur.

Disposal

Dispose in accordance with local, state, and national legislation.

Traffic

Prevent any traffic on the seams until the nora heat weld has cooled and the final trim is performed.

All traffic permitted once cooled.

Warranty

Refer to the nora Product Warranty - Americas.

Current nora Installation Instructions, Guide Specifications, Maintenance Guidelines, and Product Warranties can be found at www.nora.com.

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

Updated: June 2022