


# nora stair nosings

Rubber nosing with a slide-in lip for installation on all types of staircases. For use with noraplan® or norament® floor coverings.



## **Product Data**

Product: nora® stair nosings

- Article 802 – T 5044 A/C, E/F
- Article 805 – T 5049 A/C, E/F

Description: nora vulcanized rubber compound 961 with natural fillers and environmentally compatible color pigments that are free of toxic heavy metals like lead, cadmium, or mercury.

Material Size:

- Length: 8.2 feet (2.5 m)
- Depth: T 5049 2.0 inches (50 mm), T 5044 2.75 inches (70 mm)
- Height: T 5049 1.77 inches (45 mm), T 5044 1.69 inches (43 mm)
- Thickness: A/C 0.25 inches (6.5 mm), E/F 0.31 inches (8 mm)

Composition: Homogeneous rubber compound

Colors: 8 Standard

Surface: Smooth

## **Technical Data**

|  |  |
|--|--|
| ASTM F1861 Standard Specification for Resilient Wall Base                    | Type TP: Thermoplastic Rubber                                      |
| Flammability (E648/NFPA 253):<br>≥ 0.45 watts/sq. cm for Class 1 is required | NBSIR 75 950, 0.52   |
| Smoke Density (ASTM E662/NFPA 258):<br>< 450 is required                     | NBS, 289 (flaming) and 273 (non-flaming)                           |
| Slip Resistance (ASTM D2047):<br>≥ 0.5 is required                           | Static coefficient of friction, Neolite dry 0.95, Neolite wet 0.94 |
| Bacteria Resistance (ASTM E2180/ASTM G21):                                   | Resistant to bacteria, fungi, and micro-organism activity          |
| Hardness (ASTM D2240):   | Shore type "A", 92   |

## **Environmental Attributes**

Carbon: All flooring products 3rd party verified carbon neutral throughout their entire life cycle through the Interface Carbon Neutral Floors™ program. Learn more at [www.interface.com/carbonneutral](http://www.interface.com/carbonneutral).

Indoor Air Quality: GREENGUARD Gold Certified for Low VOC Emissions in compliance with CDPH 01350

Material Composition: Free of added formaldehyde, heavy metals and ortho-phthalates, fluorinated chemicals (PFAS), and halogenated flame retardants

Production Plant Certifications: ISO 9001:2000, ISO 14001

## **Installation**

Site Conditions: The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.

Adhesive: Use Contact cement or nora® PU MR95™.

Unique Characteristics:

- Good for very heavy traffic
- Excellent slip resistance
- High fire-retardant properties
- VI inserts available
- No coatings needed
- Allows for the installation of nora products on unusual stair designs

For complete installation instructions refer to the nora Installation Instructions.

### **Care and Cleaning**

Refer to the nora Maintenance Guidelines.

### **Wheel Types**

No metal or hard plastic wheels, the shape of the contact surface of wheels must be flat with round edges. The shore hardness must be type A ≤ 90.

### **Storage**

nora flooring can be stored within a temperature range of -5°F (-21°C) to 120°F (49°C) under the following conditions: Pallets must remain intact with sheet goods standing on end, undamaged, not be stacked, be in a permanently dry environment, and with no direct sunlight. However, all adhesives and cold weld must remain at room temperature without freezing.

### **Warranty**

Limited 5-year warranty. Refer to the nora Product Warranty - Americas.

Current nora Installation Instructions, Guide Specifications, Maintenance Guidelines, and Product Warranties, can be found at [www.nora.com](http://www.nora.com).

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

Updated: June 2022