

nora stepfix 240

Double-sided dry adhesive tape for installing norament® stairtreads. It provides a quick, clean, and easy install with no mixing or adhesive cleanup.

Product Data

Product: nora stepfix™ 240, Articles 502906

Description: A quick and easy dry adhesive tape used to install norament stairtreads.

Characteristics:

- Size/description: 9.45 inches x 164 feet (240 mm x 50 m) with wax release paper.
- Packaging: White cardboard box.



Technical Data

Shelf Life:	1 year minimum
Coverage:	Each linear foot of stair tread requires 2 linear feet of nora stepfix 240 On average, each roll covers 82 linear feet of stair tread
Storage:	Room temperature and away from direct sunlight
Moisture Limit:	≤ 75% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i>
Freeze/Thaw stable:	Stable per ASTM D7149 at 0°F (- 18°C)

Environmental Attributes

Carbon: All flooring products 3rd party verified carbon neutral throughout their entire life cycle through the Interface Carbon Neutral Floors™ program. Learn more at www.interface.com/carbonneutral.

Indoor Air Quality: GREENGUARD Gold Certified for low VOC emissions in compliance with CDPH 01350.

Material Composition: Free of organic solvents, formaldehyde, asbestos, lindane, rosins, phthalates, or any other volatile components.

VOC Content: 0 grams/liter. In compliance with the SCAQMD Rule 1168 Standard for Rubber Floor Adhesives, which has a VOC limit of 60 grams/liter.

LEED: Meets VOC emissions and content requirements of LEED.

Installation

Site Conditions: The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.

Substrate Requirements: Concrete, wood, metal, and existing floors (existing floors must be only one layer and non-cushioned back); refer to the nora Installation Instructions for details.

Unique Characteristics:

- Odorless
- No necessary open time required
- Non-flammable and freeze/thaw stable
- Easily dry fit the tread right on the covered adhesive tape, then installed stairs are ready for traffic

- Less downtime as installation area can be returned to service immediately following installation and cleaning
- For complete installation instructions refer to the nora Installation Instructions.

Disclaimer

It is the user's responsibility to read, understand and follow the nora Installation Instructions, Product Data Sheet, and Safety Data Sheet available on www.nora.com. You should comply with all applicable OSHA, local, state, and federal regulations.

Traffic

- All traffic is allowed immediately post-installation.
- Withstands heavy foot traffic.

Contact the nora Technical Department for confirmation of adhesive and flooring limits.

Warranty

Refer to the nora Product Warranty - Americas.

Current nora Installation Instructions, Guide Specifications, Maintenance Guidelines, and Product Warranties can be found at www.nora.com.

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

Updated: June 2022