

nora PU MR95

Two-component urethane adhesive designed specifically for the installation of specific nora rubber floor coverings on suitable substrates. When parts A & B are thoroughly mixed together, they form a reactive adhesive that cures to a tough, flexible film with a good resistance to surface moisture and many chemicals.


Product Data

Product: nora® PU MR95™, Article 6696

Description: A two-component urethane adhesive for the installation of specific nora rubber flooring products.

Characteristics:

- Size/description: 1.5-gallon unit within a 2-gallon pail (Parts A & B)



Technical Data

Shelf Life:	12 Months
Application:	1/32" x 1/16" x 1/32" U-notch trowel
Coverage:	~ 240 - 270 square feet per 1.5-gallon unit
Open Time:	~ 30 - 45 minutes
Working Time:	~ 120 minutes
Storage:	Room temperature and away from direct sunlight
Moisture Limit:	≤ 95% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i>
Freeze/Thaw stable:	Stable per ASTM D7149 at 0°F (- 18°C)

Environmental Attributes

Carbon: All flooring products 3rd party verified carbon neutral throughout their entire life cycle through the Interface Carbon Neutral Floors™ program. Learn more at www.interface.com/carbonneutral.

Indoor Air Quality: GREENGUARD Gold Certified for low VOC emissions in compliance with CDPH 01350.

Material Composition: Free of organic solvents, formaldehyde, asbestos, lindane, rosins, phthalates, or any other volatile components

VOC Content: < 19 grams/liter; product is in compliance with the South Coast (CA) Air Quality Management District Rule 1168 Standard for Rubber Floor Adhesives, which have a VOC limit of 60 grams/liter.

LEED Contribution: Meets VOC emissions and content requirements of LEED.

Installation

Site Conditions: The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.

Substrate Requirements: Concrete, wood, metal, and existing floors (existing floors must be only one layer and non-cushioned back); refer to the nora Installation Instructions for details. Must have an effective vapor retarder.

Unique Characteristics:

- Non-flammable and freeze/thaw stable

- If specified, hot or cold welding of flooring can commence after 12 hours

For complete installation instructions, refer to the nora Installation Instructions.

Disclaimer

It is the user's responsibility to read, understand and follow the nora Installation Instructions, Product Data Sheet, and Safety Data Sheet available on www.nora.com. You should comply with all applicable OSHA, local, state, and federal regulations.

Clean-up

Immediately remove any fresh adhesive from the surface of the flooring using 70% Isopropyl Alcohol and a clean cloth. Once cured, dried adhesive can only be mechanically removed and will damage most surfaces.

Disposal

Dispose in accordance with local, state, and federal regulations. Where possible, collect product residues and reuse. Do not allow product to get into drains, watercourses, or landfill. Collect any remaining waste material, mix both components, allow to harden, and then dispose of as Construction Waste.

Traffic

- Heavy foot traffic is allowed after 24 hours.
- Castor chairs and heavy rolling load after 48 hours.
- Withstands heavy foot traffic and heavy rolling loads.
- Withstands forklift traffic.

Contact the nora Technical Department for confirmation of adhesive and flooring limits.

Warranty

See nora Product Warranty - Americas.

For current nora Installation Instructions, Guide Specifications, Maintenance Guidelines, and Product Warranties, please visit www.nora.com.

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

Updated: June 2022