



norament grano

nora systems, Inc.
9 Northeastern Blvd.
Salem, NH 03079
T: 800.332.NORA
T: 603.894.1021
info-us@nora.com
www.nora.com

12/2023

nora[®]
by **Interface**[®]



Modern possibilities, enduring style

Create a foundation of lasting performance with norament[®] grano[™], rubber flooring that elevates interiors with unparalleled durability and versatile design. This modern take on a timeless stone aesthetic features a dense surface structure for proven strength under pressure. Stand up to even the toughest workplace conditions without sacrificing style.

Classic inspiration meets modern purpose

With one stone-inspired design, cover a wide variety of today's functional requirements. Whether you need sound reduction in education spaces, complete performance for industrial function, or ergonomic support in healthcare environments, norament grano's versatile design and a heavy-duty form gives you lasting coverage.

Reinforce the look, feel and performance of demanding interiors with norament grano.



PRODUCT NORAMENT GRANO **COLORS** 5302 ANGELICA ROOT, 5303 FRANKINCENSE,
5304 BLACK PEPPER, 5319 SPIKENARD, 5320 SASSAFRAS **INSTALLED** DIRECTIONAL

Contemporary palette, coordinating system

norament grano offers over thirty colors with modern sophistication and enduring appeal. Simplify decision-making by pairing your flooring with cross-functional stair treads, nosings or electrostatically dissipative options. The raised access option is sized to minimize waste and has factory trimmed edges, allowing raised access flooring manufacturers to easily cut to size and pre-install the flooring per individual panel.

Rubber tile flooring and stair treads combining a rich, contrasting granular design with a hammered surface for use in extremely heavy traffic areas.

norament grano
Art. 1880 32
 1004 mm x 1004 mm (~39.53 in x 39.53 in)

norament grano for raised-access panels 5
Art. 1912 5
 625 mm x 625 mm (~24.6 in x 24.6 in)

norament grano nTx
Art. 3111 16
 1004 mm x 1004 mm (~39.53 in x 39.53 in)

~3.5 mm

Product Construction Class/ASTM F1344	Homogeneous Rubber Tile Type IB and Grade 2
Surface Type	Hammered
Indoor Air Quality	GREENGUARD Gold CDPH 01350 Compliant
Full Life Cycle Carbon Emissions	Carbon Neutral Floors™
LEED v4	Contributes to multiple IEQ and MR credits

Contact your sales representative or visit nora.com for QuickShip options.

Available as **norament® grano™ nTx™**. Contact your sales representative for details and lead times.


Multiple installation options, including high-moisture solutions. View details and the full product specification at nora.com.

Installation Method




DIRECTIONAL


norament® grano™ stairtreads 12
Art. 479 - width 1285 mm (~50.59 in)
Art. 468 - width 1614 mm (~63.54 in)
Art. 469 - width 2004 mm (~78.89 in)




5301 WHITE FIR




5302 ANGELICA ROOT




5303 FRANKINCENSE




5304 BLACK PEPPER




5305 AGAR



5306 CAMPHOR




5307 FENUGREEK




5308 MYRRH




5309 JASMINE



5310 HELICHRYSUM



5311 COPAIBA




5312 VETIVER




5313 MARJORAM




5314 HENNA




5315 CEDARWOOD




5316 SIBERIAN FIR




5317 AGAPANTHUS




5318 BLUE TANSY



5319 SPIKENARD




5320 SASSAFRAS




5321 WINTERGREEN



5322 YLANG-YLANG




5323 PLUMERIA




5324 PATCHOULI




5325 BALSAM



5326 FENNEL SEED



5327 TEA TREE




5328 ARBORVITAE




5329 BERGAMOT



5330 CASSIA



5331 NEROLI



5332 GERANIUM

Welding is not required unless specified. View weld recommendations at nora.com.



Electrostatically dissipative

Safeguard your electronic devices and equipment with norament® grano™ ed – the ultimate rubber flooring solution for optimum electrostatic dissipative (ESD) protection. With a hammered surface and a dense, high performance makeup, norament grano ed offers tremendous durability ideal for clean rooms, R&D labs, electronic manufacturing plants and other ESD-sensitive applications.

- Keeps static generation consistently lower than 20V (ESD STM 97.2*)
- No conductive wax necessary with reduced maintenance that requires little more than water
- Superior stain resistance to most oils and grease
- Supported by a ten year limited conductive warranty

* Tested with conductive shoes

norament grano ed

Art. 1880  8
 □ 1002 mm x 1002 mm (~39.45 in x 39.45 in)

norament grano ed for raised-access panels

Art. 1912  5
 □ 625 mm x 625 mm (~24.6 in x 24.6 in)


 ~3.5 mm

Product Construction	Homogeneous Rubber Tile
Class/ASTM F1344	Type IB and Grade 2
Surface Type	Hammered
Indoor Air Quality	GREENGUARD Gold CDPH 01350 Compliant
Full Life Cycle Carbon Emissions	Carbon Neutral Floors™
LEED v4	Contributes to multiple IEQ and MR credits

 Contact your sales representative or visit nora.com for QuickShip options.

Can be quickly installed using [nora dryfix™ ed](#).


View details and the full product specification at nora.com.

 Designed to be pre-installed by a raised access flooring manufacturer on individual raised access panels. Not meant to overlay existing panels. The rough factory-trimmed edge must be cut to panel size for new or existing individual panels.


Installation Method




DIRECTIONAL




5301 WHITE FIR 




5304 BLACK PEPPER 




5306 CAMPHOR 



5317 AGAPANTHUS 




5318 BLUE TANSY 



5321 WINTERGREEN



5325 BALSAM



5329 BERGAMOT

Why nora® rubber flooring?

Product Benefits



Reduced Maintenance

Little more than water needed - no finishes, coatings or harsh chemicals necessary.



Quiet Acoustical Performance

Attenuate noise pollution.



Ergonomic Design

Add comfort underfoot, reducing foot and leg pain.



Durable Surface

Withstand extreme stress from heavy rolling loads and wheeled traffic.



Superior Slip Resistance

Help to create safer spaces.



Supports Infection Control

Disinfect thoroughly due to a dense, non-porous surface.

Sustainability Verifications



Carbon Neutral Floors™

Third party verified carbon neutral throughout its entire life cycle as part of Interface's Carbon Neutral Floors program. Learn more at interface.com/carbonneutral.



Cradle to Cradle Certified® Silver

Certification of whether a product is safe, circular and responsibly made. Applies to nora 926 and 913 compound floor coverings and stair treads.



GREENGUARD Gold

All nora floor coverings & adhesives are certified for low VOC emissions.



Environmental Product Declaration (EPD)

A statement of product ingredients and environmental impacts over the entire life cycle of a product. A comprehensive life cycle assessment (LCA) is performed to ISO standards to develop an EPD, after which both the EPD and LCA must be third party verified. Applies to nora 926 and 913 compound floor coverings and stair treads, and ESD and acoustic floor coverings.



Health Product Declaration (HPD)

A transparency tool for evaluating whether a product supports Green Chemistry. As part of our work on Health and Materials, Interface continuously reduces the environmental and health impacts of our products through elimination of materials of concern. Applies to nora 926 and 913 compound floor coverings and stair treads, and ESD floor coverings.

Integrated System

nora and Interface cover every area of your building – all from a single source. Create harmonious, space-specific design with our system of soft and resilient floor coverings, including special floorings, stair treads and accessories.

Outstanding Service

From design to post-installation, we have the experts to support your project at every step and can even be a valued resource for your organization's sustainability mission.

nora.com

For additional information regarding usage in recommended applications, contact us or visit nora.com.

ORDER SAMPLES

Online at www.nora.com
Call 1.800.332.NORA
Email your sales rep or customer support specialist

BROWSE NORA.COM

- Find the right floor for your project with nora Flooring Finder
- Design your floor with the nora Room Designer
- Find technical and environmental documents



We have tried our very best to accurately represent product colors. However, due to the nature of printed materials, color of actual products may vary slightly. Please request a sample to see actual product color.

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and limited warranty information, please see nora.com.

The nora brand and all other registered trademarks used in this document are registered to nora systems GmbH or its affiliates or subsidiaries. Other labels used here are trademarks of their respective owners.

PRODUCT NORAMENT GRANO COLOR 5319 SPIKENARD,
5301 WHITE FIR, 5325 BALSAM, 5302 ANGELICA ROOT
INSTALLED DIRECTIONAL