



Printed on 50% post consumer waste (PCW) fiber manufactured using wind power.



norament xp

**nora systems, Inc.**  
9 Northeastern Blvd.  
Salem, NH 03079  
T: 800.332.NORA  
T: 603.894.1021  
info-us@nora.com  
www.nora.com

02/2024

**nora**<sup>®</sup>  
by Interface<sup>®</sup>



## Hardy support for hardworking interiors

Today's high-performance workspaces must withstand the demands of daily use while inspiring the next breakthrough. Discover norament<sup>®</sup> xp<sup>™</sup>, rubber flooring that supports the world's most advanced jobs, processes and environments. With norament<sup>®</sup> xp trac<sup>™</sup>, applications challenged with recurrent wet areas will have the enhanced slip resistance and ultra-durability they need. Both have a high-impact, dense structure that resist the stresses of extreme weight and harsh chemicals, while their streamlined palette complements your high-function designs.

# Performance at its finest

Made to endure the unique demands and daily use of high-performance workspaces.

- Durable surface withstands stress from extreme weight and rolling loads
- Dense, nonporous surface creates a hygienic flooring system that can be completely disinfected
- Highly resistant to harsh chemicals and stains
- Slip resistant, reducing incidents of slip, trip, falls

norament xp trac provides enhanced slip resistance for applications challenged with recurrent wetness.



PRODUCT NORAMENT XP COLOR 5303 FRANKINCENSE INSTALLED DIRECTIONAL

© nora




PRODUCT NORAMENT XP COLOR 5303 FRANKINCENSE INSTALLED DIRECTIONAL

© nora

# Design that supports high-function


Rubber tile flooring with a choice of two granular designs – one rich in contrast and the other tone-on-tone for use in high-performance workspaces. Its high-impact, dense structure resists the stresses of extreme weight and harsh chemicals.

**norament xp**  
**Art. 1880**  16  
 □ 1004 mm x 1004 mm (~39.53 in x 39.53 in)

**norament xp nTx**  
**Art. 3111**  4  
 □ 1004 mm x 1004 mm (~39.53 in x 39.53 in)



Product Construction	Homogeneous Rubber Tile
Class/ASTM F1344	Type IB, Grade 1
Surface Type	Hammered
Indoor Air Quality	GREENGUARD Gold CDPH 01350 Compliant
LEED v4	Contributes to IEQ credits

 Available as *norament<sup>®</sup> xp™ nTx™*. Contact your sales representative for details and lead times.


Multiple installation options, including high moisture solutions.

View details and the full product specification at [nora.com](http://nora.com).

## Installation Method



DIRECTIONAL




5309 JASMINE




5109 ORION




5106 VULPECULA




5306 CAMPHOR




5102 GRUS




5110 ARA




5111 CASTOR




5303 FRANKINCENSE




5310 HELICHRYSUM



5114 CIRCINUS




5107 CALLISTO



5304 BLACK PEPPER




5330 CASSIA\*



5127 VELA



5119 MARS\*




5319 SPIKENARD


\*Use to identify sterile or restricted areas.  
 Welding is not required unless specified. View weld recommendations at [nora.com](http://nora.com).

# The solution for wet floors


Rubber tile flooring with a granular design and a structured gripping surface to meet the precise requirements of spaces with recurrent wet applications.




5306 CAMPHOR




5303 FRANKINCENSE




5304 BLACK PEPPER



5309 JASMINE



5330 CASSIA\*



5319 SPIKENARD

## norament xp trac

Art. 325



6

□ 1004 mm x 1004 mm (~39.53 in x 39.53 in)

## norament xp trac nTx

Art. 3134



4

□ 1004 mm x 1004 mm (~39.53 in x 39.53 in)



~3.5 mm

Product Construction

Class/ASTM F1344

Surface Type

Indoor Air Quality

LEED v4

Homogeneous Rubber Tile

Type IB, Grade 1

Grain Structure

GREENGUARD Gold

CDPH 01350 Compliant

Contributes to IEQ credits



Available as *norament® xp trac™ nTx™*. Contact your sales representative for details and lead times.

Multiple installation options, including high moisture solutions.

View details and the full product specification at [nora.com](http://nora.com).

## Installation Method



DIRECTIONAL

\*Use to identify sterile or restricted areas.

Welding is not required unless specified. View weld recommendations at [nora.com](http://nora.com).

## Why nora® rubber flooring?

### Product Benefits



#### Reduced Maintenance

Little more than water needed - no finishes, coatings or harsh chemicals necessary.



#### Quiet Acoustical Performance

Attenuate noise pollution.



#### Ergonomic Design

Add comfort underfoot, reducing foot and leg pain.



#### Durable Surface

Withstand extreme stress from heavy rolling loads and wheeled traffic.



#### Superior Slip Resistance

Help to create safer spaces.



#### Supports Infection Control

Disinfect thoroughly due to a dense, non-porous surface.

### Sustainability Verifications



#### Cradle to Cradle Certified® Silver

Certification of whether a product is safe, circular and responsibly made. Applies to nora 926 and 913 compound floor coverings and stair treads.



#### GREENGUARD Gold

All nora floor coverings & adhesives are certified for low VOC emissions.



#### Environmental Product Declaration (EPD)

A statement of product ingredients and environmental impacts over the entire life cycle of a product. A comprehensive life cycle assessment (LCA) is performed to ISO standards to develop an EPD, after which both the EPD and LCA must be third party verified. Applies to nora 926 and 913 compound floor coverings and stair treads, and ESD and acoustic floor coverings.



#### Health Product Declaration (HPD)

A transparency tool for evaluating whether a product supports Green Chemistry. As part of our work on Health and Materials, Interface continuously reduces the environmental and health impacts of our products through elimination of materials of concern. Applies to nora 926 and 913 compound floor coverings and stair treads, and ESD floor coverings.

### Integrated System

nora and Interface cover every area of your building – all from a single source. Create harmonious, space-specific design with our system of soft and resilient floor coverings, including special floorings, stair treads and accessories.

### Outstanding Service

From design to post-installation, we have the experts to support your project at every step and can even be a valued resource for your organization's sustainability mission.

### nora.com

For additional information regarding usage in recommended applications, contact us or visit [nora.com](http://nora.com).

➤ **ORDER SAMPLES**  
Online at [www.nora.com](http://www.nora.com)  
Call 1.800.332.NORA  
Email your sales rep or customer support specialist

#### BROWSE NORA.COM

- Find the right floor for your project with nora Flooring Finder
- Design your floor with the nora Room Designer
- Find technical and environmental documents

We have tried our very best to accurately represent product colors. However, due to the nature of printed materials, color of actual products may vary slightly. Please request a sample to see actual product color.

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and limited warranty information, please see [nora.com](http://nora.com).

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. Cradle to Cradle Certified® is a registered trademark of the Cradle to Cradle Products Innovation Institute. Other labels used here are trademarks of their respective owners.

PRODUCT NORAMENT XP COLOR 5303 FRANKINCENSE  
INSTALLED DIRECTIONAL