



Printed on 50% post consumer waste (PCW) fiber manufactured using wind power.



Errors as well as misprints and changes reserved. No guarantee is given for the accuracy and completeness of the information. The product images in this document may differ from the original. This document is not a contractual offer and only serves to provide non-binding information.

The nora brand and all other registered trademarks used in this document are registered to nora systems GmbH or its affiliates or subsidiaries. Other labels used here are trademarks of their respective owners.

**nora systems, Inc.**  
9 Northeastern Blvd.  
Salem, NH 03079  
T: 800.332.NORA  
T: 603.894.1021  
info-us@nora.com  
www.nora.com

11/2023 Form Order #810050

# noraplan dariva

**nora**<sup>®</sup>  
by Interface<sup>®</sup>



## Beauty of nature, benefits of rubber

Outdoors, there is an abundant use of soft, tonal color. We see it in everything from stones, clays, watery ripples and sprigs of greenery to the lavender cast of twilight. noraplan dariva™ features earthy, muted tones and soft marbling to connect us to the sense of awe we find in nature's colors.

Its smooth surface and dense rubber structure support human-centered needs like reduced noise and underfoot comfort as well as operational challenges like high-traffic, frequent hygiene protocols and heavy rolling loads. For everywhere from noisy cafeterias to sterile operating rooms, noraplan dariva unites beauty with performance for a biophilic and holistic design solution.





# Soft appearance, tough performance

noraplan dariva connects us to nature's use of color, drawing us in and supporting soothing environments. And, it offers the best of noraplan®. With a functional smooth surface and earthy design, it conceals dirt between cleanings, stands up to stringent maintenance protocols in sterile areas, and delivers the high noraplan standards for durability, ergonomics, acoustics, safety and maintenance.

Pair it with nora sanitary base, coordinating noraplan® valua™ or Interface® carpet and LVT for space-specific solutions across your entire facility.

Rubber sheet flooring with tonal color, organic marbling and a smooth surface for use in heavy traffic areas.

## noraplan dariva 2 mm

Art. 160F  28  
 15 m x 1.22 m (~49.21 ft x 48 in)


 ~2 mm

## noraplan dariva 3 mm

Art. 161F  28  
 12 m x 1.22 m (~39.37 ft x 48 in)

 ~3 mm

Product Construction	Homogeneous Rubber Sheet
Class/ASTM F1859	Type I
Surface Type	Smooth
Indoor Air Quality	GREENGUARD Gold
Full Life Cycle Carbon Emissions	CDPH 01350 Compliant
LEED v4	Carbon Neutral Floors™
	Contributes to multiple IEQ and MR credits

 Sheet available as noraplan dariva™ nTx™. Contact your sales representative for details and lead times.


Multiple installation options, including high-moisture solutions.

View details and the full product specification at [nora.com](http://nora.com).

## Installation Method



DIRECTIONAL



7161 PINE NUT



6716 ALMOND



6714 MUSHROOM



6713 BIRCH



7164 HICKORY



6718 WALNUT



6721 SANDBAR



6709 SMOKE




7168 ARGAN



6715 PECAN



6722 PINECONE



7169 RIVER BIRCH



7173 RED MAPLE



6719 COCOA BEAN



6723 BARK



6710 CHARCOAL


Welding is not required unless specified. View weld recommendations at [nora.com](http://nora.com).



7162 COTTONWOOD



6708 BEACH WOOD



7163 PLANTAIN



7165 PEPPERWOOD



7166 PALMETTO



7167 JUNIPER



7170 ACAI BERRY



7171 BLUE SPRUCE



7172 SYCAMORE



7174 BLUEBELL



7175 WISTERIA



7176 HEMLOCK





## Why nora® rubber flooring?



### Reduced Maintenance

Little more than water needed - no finishes, coatings or harsh chemicals necessary.



### Quiet Acoustical Performance

Attenuate noise pollution.



### Durable Surface

Withstand extreme stress from heavy rolling loads and wheeled traffic.



### Ergonomic Design

Add comfort underfoot, reducing foot and leg pain.



### Superior Slip Resistance

Help to create safer spaces.



### Supports Infection Control

Disinfect completely due to a dense, non-porous surface.



### Cradle to Cradle Certified® Silver

Certification of whether a product is safe, circular and responsibly made. Applies to nora 926 and 913 recipe flooring and stair treads.



### Carbon Neutral Floors™

Third party verified carbon neutral throughout its entire life cycle as part of Interface's Carbon Neutral Floors program. Learn more at [interface.com/carbonneutral](https://interface.com/carbonneutral)



### GREENGUARD Gold

Certified low VOC emissions.

## Integrated system

nora and Interface cover every area of your building – all from a single source. Create harmonious, space-specific design with our system of soft and resilient floor coverings, including special floorings, stair treads and accessories.

## Outstanding service

From design to post-installation, we have the experts to support your project at every step and can even be a valued resource for your organization's sustainability mission.

For additional information regarding usage in recommended applications, contact us or visit [nora.com](https://nora.com).

➤ **ORDER SAMPLES**  
 Online at [www.nora.com](https://www.nora.com)  
 Call 1.800.332.NORA  
 Email your sales rep or customer support specialist

**BROWSE NORA.COM**

- Design your floor with the nora Room Designer
- Find technical and environmental documents
- Access BIM/Revit Files

## Limited warranty

We will be happy to supply specific test results on all nora systems, Inc. products.

### nora® by Interface®

#### Limited Warranty – Americas (Excerpt)

nora systems, Inc. (nora) warrants the following nora® brand products (collectively, the "Warranted nora Brand Flooring Products") as set forth below: norament® and noraplan® rubber flooring, norament rubber stairtread (excluding visually impaired strips), accessories (excluding visually impaired strips), nora® nTx™ 020 bond enhancer and adhesives, and the conductivity of its Electrostatic Dissipative ("ESD") flooring system (norament ed and noraplan ed flooring and adhesive).

This limited warranty and the applicable Installation Instructions and Maintenance Guidelines are subject to change at nora's discretion and without notice. Please contact nora or visit the [nora.com](https://nora.com) website for the latest versions. For additional information regarding usage in recommended applications, please refer to [www.nora.com](https://www.nora.com) or call 1-800-332-NORA. Warranty periods commence on the date of invoice of the product to the original end-use customer.